

Principal dimensions (mm)			Basic load ratings (KN)		Pu	Speed ratings rpm (r/min)		Weight (kg) (Bearing+ Withdrawal sleeves)	Designation	Dimensions (mm)											Abutment and fillet dimensions (mm)				Value			
基本尺寸			基本额定负荷			疲劳负荷极限	额定转速			质量 (轴承+退卸套)	型号	尺寸											挡肩及倒角尺寸				计算系数	
d	D	B	dyc Cr	stc Cor	Speed Ratings		Limiting Speed	Bearing	Withdrawal sleeves			d <sub>1</sub>	d <sub>2</sub>	D1	B <sub>1</sub>	B <sub>2</sub> <sup>1)</sup>	G	G <sub>1</sub>	b	k	r <sub>1,2</sub> Min	da Min	Da Max	ra Max	e	Y1	Y2	Yo
			动态	静态		参考转速				极限转速	r <sub>1,2</sub> 最小										da 最小	Da 最大	ra 最大					
360	620	194	4400	7100	500	560	1000	250	*23176CAK/W33	AOH3176G	360	452	541	232	242	Tr400×5	36	22.3	12	5	400	600	4	0.30	2.3	3.4	2.2	
380	650	200	4650	7650	530	530	950	290	*23180CAK/W33	AOH3180G	380	474	566	240	250	Tr420×5	38	22.3	12	6	426	624	5	0.28	2.4	3.6	2.5	
420	720	226	6000	10000	670	450	850	380	*23188CAK/W33	AOHX3188G	420	528	632	270	281	Tr460×5	48	22.3	12	6	466	694	5	0.30	2.3	3.4	2.2	
440	760	240	6400	10800	680	430	800	465	*23192CAK/W33	AOHX3192G	440	553	666	285	296	Tr480×5	43	22.3	12	7.5	492	728	6	0.30	2.3	3.4	2.2	
460	790	248	6950	12000	780	400	750	515	*23196CAK/W33	AOHX3196G	460	577	692	295	307	Tr500×5	45	22.3	12	7.5	512	758	6	0.30	2.3	3.4	2.2	
480	830	264	7650	12900	830	380	700	610	*231500CAK/W33	AOHX31500G	480	603	726	313	325	Tr530×6	47	22.3	12	7.5	532	798	6	0.30	2.3	3.4	2.2	
500	870	272	8150	14000	915	360	670	715	*231530CAK/W33	AOH31530	500	636	763	325	337	Tr560×6	53	22.3	12	7.5	562	838	6	0.30	2.3	3.4	2.2	
530	920	280	9150	16000	980	340	630	850	*231560CAK/W33	AOH31560	530	673	809	335	347	Tr600×6	55	22.3	12	7.5	592	888	6	0.30	2.3	3.4	2.2	
570	980	300	10200	18000	1100	320	560	1010	*231600CAK/W33	AOHX31600	570	720	863	355	369	Tr630×6	55	22.3	12	7.5	632	948	6	0.30	2.3	3.4	2.2	
600	1030	315	10500	20800	1220	260	530	1190	231630CAK/W33	AOH31630	600	755	918	375	389	Tr670×6	60	22.3	12	7.5	662	998	6	0.30	2.3	3.4	2.2	
630	1090	336	10900	22400	1370	240	500	1430	231670CAK/W33	AOHX31670	630	802	959	395	409	Tr710×7	59	22.3	12	7.5	702	1058	6	0.30	2.3	3.4	2.2	
670	1150	345	12200	26000	1530	240	450	1650	231710CAK/W33	AOHX31710	670	850	1097	405	421	Tr750×7	60	22.3	12	9.5	750	1110	8	0.28	2.4	3.6	2.5	
710	1220	365	13800	29000	1660	220	430	1930	231750CAK/W33	AOH31750	710	900	1080	425	441	Tr800×7	60	22.3	12	9.5	790	1180	8	0.28	2.4	3.6	2.5	
750	1280	375	14800	31500	1800	200	400	2200	231800CAK/W33	AOH31800	750	950	1141	438	456	Tr850×7	63	22.3	12	9.5	840	1240	8	0.28	2.4	3.6	2.5	
800	1360	400	16100	34500	2000	180	360	2500	231850CAK/W33	AOH31850	800	1010	1205	462	480	Tr900×7	62	22.3	12	12	898	1312	10	0.28	2.4	3.6	2.5	
950	1580	462	21400	48000	2550	140	280	3950	2311000CAK/W33	AOH311000	950	1182	1403	525	547	Tr1060×8	63	22.3	12	12	1048	1532	10	0.28	2.4	3.6	2.5	