

Principal dimensions (mm)			Basic load ratings (KN)		Pu	Speed ratings rpm (r/min)		Weight (kg) (Bearing* Withdrawal sleeves)	Designation		Dimensions (mm)										Abutment and fillet dimensions (mm)			Value			
基本尺寸			基本额定负荷			额定转速			型号		尺寸										挡肩及倒角尺寸			计算系数			
d	D	B	dyc Cr	sto Cor	疲劳负荷极限	Speed Ratings	Limiting Speed	质量 (轴承+退卸套)	Bearing	Withdrawal sleeves	d <sub>1</sub>	d <sub>2</sub>	D1	B <sub>1</sub>	B <sub>2</sub> <sup>(1)</sup>	G	G <sub>1</sub>	b	k	r <sub>1,2</sub>	da Min	Da Max	ra Max	e	Y1	Y2	Yo
			动态	静态		参考转速	极限转速		轴承	退卸套		~	~							Min	da 最小	Da 最大	ra 最大				
400	700	224	5600	9300	620	480	900	375	*23184CKJ/W33	AOH3184G	400	483	607	266	276	Tr440	40	22.3	12	6	446	674	5	0.30	2.3	3.4	2.2
530	920	355	12000	21600	1340	280	500	1060	*241/560ECK30J/W33	AOH241/560G	530	634	796	393	417	Tr600	38	22.3	12	7.5	592	888	6	0.35	1.9	2.9	1.8
600	920	290	8800	18000	1140	320	530	730	*240/630ECK30J/W33	AOH240/630G	600	697	823	330	356	Tr670	40	22.3	12	7.5	658	892	6	0.28	2.4	3.6	2.5