

Principal dimensions (mm)			Basic load ratings (KN)		P <sub>u</sub>	Speed ratings rpm (r/min)		Weight (kg)	Designation		Dimensions (mm)						Abutment and fillet dimensions (mm)					Value		
基本尺寸			基本额定负荷			额定转速			型号		尺寸						挡肩及倒角尺寸					计算系数		
d <sub>i</sub>	D	B	dyc Cr	stc Cor	疲劳负荷极限	Speed Ratings	Limiting Speed	质量	Cylindrical Bore	Taper Bore	d	d <sub>2</sub>	D <sub>1</sub>	r <sub>1,2</sub>	s <sub>1</sub> <sup>(1)</sup>	s <sub>2</sub> <sup>(1)</sup>	d <sub>a</sub>	d <sub>e</sub>	D <sub>a</sub>	D <sub>e</sub>	C <sub>a</sub> <sup>(2)</sup>	r <sub>a</sub>	k <sub>1</sub>	k <sub>2</sub>
			动态	静态		参考转速	极限转速		圆柱孔	圆锥孔														
90	150	72	455	670	73.5	-	1500	5.10	*BSC-2039V	-	90	109	131	2	19.7	19.7	101	115	-	139	-	2	0.087	0.123
100	170	65	475	655	69.5	-	1400	5.95	*BSC-2034V	-	100	120	148	2	17.7	17.7	111	130	-	159	-	2	0.09	0.125