

Principal dimensions (mm)			Basic load ratings (kN)		P _u	Speed ratings rpm (r/min)		Weight (kg) (Bearing+ Withdrawal sleeves)	Designation		Dimensions (mm)								Abutment and fillet dimensions (mm)						Value			
基本尺寸			基本额定负荷			额定转速			质量 (轴承+退卸套)	型号		尺寸								挡肩及倒角尺寸						计算系数		
d1	D	B	dyc Cr	stc Cor	疲劳负荷极限	Speed Ratings	Limiting Speed	Bearing		Withdrawal sleeves	d ₁	d ₂	d ₃	D1	B ₁	B ₂	r _{1,2} Min	s ₁ ⁰	s ₂ ¹	da Max	db Min	Da Min	Da Max	B _a Min	Ca Min	ra Max	k ₁	k ₂
			动态	静态		参考转速	极限转速		轴 承								退卸套	r _{1,2} 最小	~									
25	62	20	69.5	62	7.2	11000	15000	0.37	*C2206KTN9	H306E	25	37.4	45	53.1	31	10.5	1	4.5	-	37	33	51	56.4	5	0.3	1	0.101	0.111
30	72	23	83	80	9.3	9500	13000	0.59	*C2207KTN9	H307E	30	44.8	52	60.7	35	11.5	1.1	5.7	-	44	39	59	65	5	0.1	1	0.094	0.121
35	80	23	90	86.5	10.2	8000	11000	0.69	*C2208KTN9	H308E	35	52.4	58	69.9	36	13	1.1	7.1	-	52	44	68	73	5	0.3	1	0.093	0.128
40	85	23	93	93	10.8	8000	11000	0.76	*C2209KTN9	H309E	40	55.6	65	73.1	39	13	1.1	7.1	-	55	50	71	78	7	0.3	1	0.095	0.128
45	90	23	98	100	11.8	7000	9500	0.85	*C2210KTN9	H310E	45	61.9	70	79.4	42	14	1.1	7.1	-	61	55	77	83	9	0.8	1	0.097	0.128
50	100	25	116	114	13.4	6700	9000	1.10	*C2211KTN9	H311E	50	65.8	75	86.7	45	14	1.5	8.6	-	65	60	84	91	10	0.3	1.5	0.094	0.133
55	110	28	143	156	18.3	5600	7500	1.45	*C2212KTN9	H312E	55	77.1	80	97.9	47	14	1.5	8.5	-	77	65	95	101	9	0.3	1.5	0.1	0.123
60	120	31	180	180	21.2	5300	7500	1.80	*C2213KTN9	H313E	60	79	85	106	50	15	1.5	9.6	-	79	70	102	111	8	0.2	1.5	0.097	0.127
60	125	31	186	196	23.2	5000	7000	2.10	*C2214KTN9	H314E	60	83.7	92	111	52	15	1.5	9.6	-	83	75	107	116	9	0.4	1.5	0.098	0.127