

Principal dimensions (mm)			Basic load ratings (KN)		Pu	Min Loading A	Speed ratings rpm (r/min)		Weight (kg)	Designation	Dimensions mm						Abutment and fillet dimensions mm			Designations		
基本尺寸			基本额定负荷				额定转速				尺寸						挡肩及倒角尺寸			各部件型号		
d	D	H	dyc Cr	stc Cor	疲劳负荷极限	最小负荷	Speed Ratings	Limiting Speed	质量	型号	d	d <sub>1</sub> ~	D <sub>1</sub> ~	B	D <sub>w</sub>	r <sub>1,2</sub> Min	da Min	Da Max	ra Max	Cylindrical Rollers - Cage Assemblies	Shaft washer	Housing washer
			动态	静态		A	参考转速	极限转速								r <sub>1,2</sub> 最小	da 最小	Da 最大	ra 最大			
140	200	46	360	1400	129	0.16	700	1400	4.55	81228M	140	197	143	13.5	19	1.5	191	147	1.5	K81228M	WS81228	GS81228
150	215	50	465	1900	170	0.29	630	1300	5.90	81230M	150	212	153	14.5	21	1.5	211	158	1.5	K81230M	WS81230	GS81230
160	225	51	480	2000	176	0.32	600	1200	6.20	81232M	160	222	163	15	21	1.5	220	168	1.5	K81232M	WS81232	GS81232
170	240	55	540	2280	200	0.42	560	1100	7.70	81234M	170	237	173	16.5	22	1.5	235	180	1.5	K81234M	WS81234	GS81234
180	225	34	270	1270	110	0.13	750	1500	3.05	81136M	180	222	183	10	14	1.1	219	185	1	K81136M	WS81136	GS81136
180	250	56	550	2400	204	0.46	560	1100	8.25	81236M	180	247	183	17	22	1.5	245	190	1.5	K81236M	WS81236	GS81236
190	240	37	310	1460	125	0.17	700	1400	3.85	81138M	190	237	193	11	15	1.1	233	197	1	K81138M	WS81138	GS81138
190	270	62	695	2900	250	0.67	500	1000	10.5	81238M	190	267	194	18	26	2	265	200	2	K81238M	WS81238	GS81238
200	250	37	310	1500	127	0.18	700	1400	4.00	81140M	200	247	203	11	15	1.1	243	206	1	K81140M	WS81140	GS81140
200	280	62	720	3100	255	0.77	500	1000	12.0	81240M	200	277	204	18	26	2	275	210	2	K81240M	WS81240	GS81240
220	270	37	335	1700	137	0.23	670	1300	4.50	81144M	220	267	223	11	15	1.1	263	226	1	K81144M	WS81144	GS81144
220	300	63	750	3350	275	0.90	480	950	13.0	81244M	220	297	224	18.5	26	2	296	230	2	K81244M	WS81244	GS81244