

Dimensions (mm)												Speed ratings rpm (r/min)	Weight (kg)	Designation	
尺寸												额定转速(r/min)		型号	
d	A	B	H	H ₁	H ₂	J	L	N	N ₁	G	s ₁	stc Cor	质量	Y-Bearing with pressed steel cages	Y-Bearing with graphite cages
												静态		带冲压钢保持架的Y-轴承单元	带石墨冠状保持架的Y-轴承单元
3/4	32	31	64	33,3	14	97	127	20,5	11,5	10	18,3	6,55	0,57	SY3/4TF/VA201	SY3/4TF/VA228
1	36	34,1	70	36,5	16	102	130	19,5	11,5	10	19,8	7,8	0,73	SY1.TF/VA201	SY1.TF/VA228
1 3/16	40	38,1	82	42,9	17	117,5	152	23,5	14	12	22,2	11,2	1,10	SY1.3/16TF/VA201	SY1.3/16TF/VA228
1 1/4	45	42,9	93	47,6	19	126	160	21	14	12	25,4	15,3	1,45	SY1.1/4TF/VA201	SY1.1/4TF/VA228
1 1/16	45	42,9	93	47,6	19	126	160	21	14	12	25,4	15,3	1,45	SY1.7/16TF/VA201	SY1.7/16TF/VA228
1 1/2	48	49,2	99	49,2	19	135,5	175	24,5	14	12	30,2	19	1,80	SY1.1/2TF/VA201	SY1.1/2TF/VA228
1 11/16	48	49,2	107	54	20,6	143,5	187	22,5	14	12	30,2	21,6	2,2	SY1.11/16TF/VA201	SY1.11/16TF/VA228
1 3/4	48	49,2	107	54	20,6	143,5	187	22,5	14,5	12	30,2	21,6	2,20	SY1.3/4TF/VA201	SY1.3/4TF/VA228
1 15/16	54	51,6	114	57,2	22	157	203	26	18	16	32,6	23,2	2,70	SY1.15/16TF/VA201	SY1.15/16TF/VA228
2	60	55,6	127	63,5	23,8	171,5	219	27,5	18	16	33,4	29	3,60	SY2.TF/VA201	SY2.TF/VA228
2 3/16	60	55,6	127	63,5	23,8	171,5	219	27,5	18	16	33,4	29	3,55	SY2.3/16TF/VA201	SY2.3/16TF/VA228
2 7/16	60	65,1	139,7	69,9	26	190,5	240	29	18	16	39,7	36	4,45	SY2.7/16TF/VA201	SY2.7/16TF/VA228