

Bearing No.	Shaft Dia d		Dimensions(mm)								Basic load ratings (KN)		Weight (kg)
	轴径		尺寸								基本额定负荷		
	(in)	(mm)	D	L	d	Bi	Be	T	y	w	dyc Cr	stc Cor	质量
											动态	静态	
UK205+HE2305	3/4		52	35	25	23	17	4.5	8	38	1100	710	0.25
UK205+HA2305	13/16		52	35	25	23	17	4.5	8	38	1100	710	0.24
UK205+H2305		20	52	35	25	23	17	4.5	8	38	1100	710	0.24
UK206+HS2306	7/8		62	38	30	26	19	5.1	8	45	1540	1020	0.42
UK206+HA2306	15/16		62	38	30	26	19	5.1	8	45	1540	1020	0.41
UK206+HE2306	1		62	38	30	26	19	5.1	8	45	1540	1020	0.37
UK206+H2306		25	62	38	30	26	19	5.1	8	45	1540	1020	0.4
UK207+HS2307	1-1/8		72	43	35	27	20	5.8	9	52	2030	1400	0.57
UK207+HA2307	1-3/16		72	43	35	27	20	5.8	9	52	2030	1400	0.55
UK207+H2307		30	72	43	35	27	20	5.8	9	52	2030	1400	0.55
UK208+HE2308	1-1/4		80	46	40	29	21	6.2	10	58	2300	1600	0.78
UK208+HA2308	1-5/16		80	46	40	29	21	6.2	10	58	2300	1600	0.75
UK208+HS2308	1-3/8		80	46	40	29	21	6.2	10	58	2300	1600	0.72
UK208+H2308		35	80	46	40	29	21	6.2	10	58	2300	1600	0.72
UK209+HA2309	1-7/16		85	50	45	30	22	6.5	11	65	2560	1810	0.89
UK209+HE2309	1-1/2		85	50	45	30	22	6.5	11	65	2560	1810	0.84
UK209+HS2309	1-5/8		85	50	45	30	22	6.5	11	65	2560	1810	0.77
UK209+H2309		40	85	50	45	30	22	6.5	11	65	2560	1810	0.8
UK210+HA2310	1-11/16		90	55	50	31	23	6.5	12	70	2750	2020	0.98
UK210+HE2310	1-3/4		90	55	50	31	23	6.5	12	70	2750	2020	0.95
UK210+H2310		45	90	55	50	31	23	6.5	12	70	2750	2020	0.93
UK211+HS2311	1-7/8		100	59	55	33	24	7.3	12	75	3400	2550	1.28
UK211+HA2311	1-15/16		100	59	55	33	24	7.3	12	75	3400	2550	1.22
UK211+HE2311	2		100	59	55	33	24	7.3	12	75	3400	2550	1.17

UK211+H2311		50	100	59	55	33	24	7.3	12	75	3400	2550	1.19
UK212+HA2312	2-1/16		110	62	60	36	26	7.7	13	80	4100	3150	1.62
UK212+HS2312	2-1/8		110	62	60	36	26	7.7	13	80	4100	3150	1.56
UK212+H2312		55	110	62	60	36	26	7.7	13	80	4100	3150	1.52
UK213+HA2313	2-3/16		120	65	65	38	27	8.3	14	85	4480	3470	2.1
UK213+HE2313	2-1/4		120	65	65	38	27	8.3	14	85	4480	3470	2.04
UK213+HS2313	2-3/8		120	65	65	38	27	8.3	14	85	4480	3470	1.89
UK213+H2313		60	120	65	65	38	27	8.3	14	85	4480	3470	1.91
UK215+HA2315	3/258		130	73	75	41	30	9.2	15	98	5200	4200	2.65
UK215+H2315		65	130	73	75	41	30	9.2	15	98	5200	4200	2.56
UK216+HE2316	2-3/4		140	78	80	44	32	9.6	17	105	5700	4550	3.24
UK216+H2316		70	140	78	80	44	32	9.6	17	105	5700	4550	3.23
UK217+HE2317	3		150	82	85	46	34	10.5	18	110	6600	5320	3.84
UK217+H2317		75	150	82	85	46	34	10.5	18	110	6600	5320	3.93
UK218+HS2318	3-1/8		160	86	90	49	36	11.1	18	120	7550	6170	4.8
UK218+H2318		80	160	86	90	49	36	11.1	18	120	7550	6170	4.75